

ACCESSORIES

Hand transmitter BLACK	Hand transmitter MAX	Hand transmitter Multibit	SafeControl	DigitCode	Light barrier	Emergency release	Warning light	Signal lamps	Pull button	Closing edge	Key switch	Push button	Accu pack	Solar module	Door fittings	LED board
---------------------------	-------------------------	------------------------------	-------------	-----------	---------------	-------------------	---------------	--------------	-------------	--------------	------------	-------------	-----------	--------------	---------------	-----------

GARAGE DOOR OPERATORS

BLACK 600	●	●	●	●	●	●	●	●	●	3)	●	●			●	
BLACK 800	●	●	●	●	●	●	●	●	●	3)	●	●			●	
BLACK 1000	●	●	●	●	●	●	●	●	●	3)	●	●			●	
BLACK 1200	●	●	●	●	●	●	●	●	●	3)	●	●			●	
RUN 500	●	●	●	●	●	●	●	●	●	●	●	●			●	
RUN 700	●	●	●	●	●	●	●	●	●	●	●	●			●	
RUN 500 Accu	●	●	●	●	●	●	●	●	●	3)	●	●	●	●	●	

INDUSTRIAL CONTROL UNITS & OPERATORS

NovoCon T 50 NDES	●	1)	●								●	●				
NovoCon T 75 DES	●	●	●	●	●		●	●	●	●	●	●				
NovoCon T 100 DES / NDES / R / R-FU	●	●	●	●	●		●	●	●	●	●	●				
NovoShaft	●	●	●	●	●		●	●	●	●	●	●				
GTA 4000	●	●	●	●	●	●	●	●	●	●	●	●			●	

OPERATORS FOR GATES

NovoSwing	●	●	● 3)	●	●	integrated				● 3)	●	●				
PowerSwing	●	●	●	●	●	●	●	●	●	3)	●	●				
400 SB, CBAC, SB Langhub 2)	●	●	●	●	●	●	●	●	●	3)	●	●				
402 CBC 2)	●	●	●	●	●	●	●	●	●	3)	●	●				
750 SB, CBAC 2)	●	●	●	●	●	●	●	●	●	3)	●	●				
S 800 H SB, CBAC 2) 24 V or 230 V	●	●	●	●	●	●	●	●	●	3)	●	●				
413 24 V	●															

Hinged gates

NovoGate	●	●	● 4)	●	●	integrated				● 3)						
PowerSlide	●	● 4)	●	●	●	●	●	●	●	●						
C721	●	● 4)	●	●	●	●	●	●	●	3)	●	●				
741 EZ16	●	● 4)	●	●	●	●	●	●	●	3)	●	●				
844 ER Z16	●	● 4)	●	●	●	●	●	●	●	3)	●	●				

Sliding gates

1) UHF receiver module required. 2) Control unit required. 3) With additional evaluation unit. 4) With receiver E43-1 only.

RADIO SYSTEMS

HAND TRANSMITTER



Hand transmitter BLACK Remote

3-channel hand transmitter, 433 MHz, with KeeLoq rolling code

201220-02-1-50



Hand transmitter Design

2-channel hand transmitter in carbon optics, 433 MHz, with KeeLoq rolling code

020410-31-3-32



Micro hand transmitter MIX 43-2

2-channel hand transmitter, 433 MHz, with KeeLoq rolling code

020437-31-3-32



Hand transmitter MAX 43-2

2-channel hand transmitter, 433 MHz, with KeeLoq rolling code

020429-31-3-32



Hand transmitter MAX 43-4

4-channel hand transmitter, 433 MHz, with KeeLoq rolling code

020431-31-3-32



Wall mount for hand transmitters

With sun visor clip for MAX 43-2, MAX 43-4 ⁽¹⁾ and MIX 43-2 ⁽²⁾

⁽¹⁾ 020229-31-3-32

⁽²⁾ 020250-31-3-32



Hand transmitter Multibit

1-channel hand transmitter, 433 MHz, with Multibit code

020001-31-3-32



Hand transmitter Multibit

4-channel hand transmitter, 433 MHz, with Multibit code

020002-31-3-32



Hand transmitter MultiKee

4-channel hand transmitter, 433 MHz, with KeeLoq rolling code and Multibit code

020254-31-3-32

IMPULSE SENSORS

**Push button DigiCode Premium**

Metal keyboard, 433 MHz, with KeeLoq rolling code

148710-40-1-50

**Push button DigiCode Professional**

Foil keyboard, 433 MHz, with KeeLoq rolling code

148700-40-1-50

**Push button DuoControl**

433 MHz, with KeeLoq rolling code

148740-40-1-50

**Touch contact Save Control**

Vacation lock, start, continuous light

148720-51-1-50

**Touch contact 5 m**

With 5 m cable

020020-31-3-32

**Touch contact 7 m**

With 7 m cable

147738-01-1-50

**Pull cord contact ZT AP**

Tethered, accessories included

000904-10-0-20

**Key switch KT 3 / 1 AP**

Single impulse, on-wall

020024-31-3-32

**Key switch KT 3 / 1 UP**

Single impulse, flush-mounted

020023-31-3-32

**Key switch KT 8 UP**

Double impulse, flush-mounted

050548-31-3-32

**Key switch KT 8 AP**

Double impulse, on-wall

050549-31-3-32

IMPULSE SENSORS



Code touch contact MTB 24

3 relay contacts, with metal keyboard and electronic module, 24 V

148123-03-1-50



Code touch contact MTB 230

3 relay contacts, with metal keyboard and electronic module, 230 V

148124-03-1-50



Finger print Biokey

For 150 memory spaces

020220-31-3-32

RADIO RECEIVERS



Receiver E43-U

In housing, for KeeLoq and Multibit, with 1 relay output, records 99 codes

157250-01-1-50



Receiver E43-ST

In housing, for KeeLoq, 1 relay output, records 13 codes

020189-31-3-32




Receiver E43-1 and -2

In housing, for KeeLoq, 1 ⁽¹⁾ respectively 2 ⁽²⁾ relay outputs, records 99 codes

⁽¹⁾ 157251-01-1-50

⁽²⁾ 157252-01-1-50



Maxi Receiver E43-XL

In housing, for KeeLoq, 4 relay outputs, records 1000 codes

020192-31-3-32



Receiver E43-I

Without housing, for KeeLoq and Multibit, 1 relay output, records 99 codes

157255-01-1-50



Receiver module with antenna 433 MHz

For garage door operators and com. control units, radio receiver 433 MHz and traffic light control

150638-01-1-50



Coaxial antenna

With 5 m connection cable

150449-01-1-50



Bar antenna type A 43

With 6.5 m connection cable

000904-50-0-84

STANDARD

DOOR FITTINGS



Door fitting standard

For up-and-over and sectional doors

150445-03-1-50



Special door fitting

Flat special version for up-and-over and sectional doors

150445-05-1-40



Fitting for sectional doors

For sectional doors with a slat height of 360 - 565 mm

150427-02-1-50



All-purpose fitting

For mounting with lintel for 450 - 610 mm lintel depth


147105-11-1-50



1-piece door fitting

For double-leafed garage doors with a leaf width of 1600 mm

147669-01-1-50



Curved arm door fitting complete

For gates with vertical guide rail, which cannot swing up

000939-06-1-08

Limited availability



Pull rod extension LS 2700

For backwards shifted operators, adjustable length of pull rod 1600 - 2700 mm

147071-01-1-50



Central additional locking

Complete for up-and-over doors

150451-01-1-50

EMERGENCY RELEASES



Emergency release for up-and-over doors

With an interior string length of 5 m

147061-47-1-50



Emergency release for sectional doors

Installation material included

147061-48-1-50



Emergency release with round cylinder

For double-leafed doors, sliding overhead and sectional garage doors

147004-01-1-50



Emergency release with profile cylinder

For double-leafed doors, sliding overhead and sectional garage doors

020241-31-3-32

ACCU & SOLAR


Accu pack


Auxiliary accumulator for RUN 500 Accu

157200-01-1-50


Solar module

For RUN 500 Accu, fastening bracket included

157170-01-1-50


APS 230 accu power system

For garage door operators, acoustic warning signal, wall mounting and integrated loading regulator

157220-01-1-50


APS 230 solar module

Module holder is adjustable from 0° - 45°, with 8 m connecting cable

020217-31-3-32


APS 230 accu pack

Auxiliary accumulator

157200-03-1-50


APS 230 modifier

Basis station SW 150-12 V

020199-31-3-32

RADIO SYSTEMS

TRANSMITTER & RECEIVER



**Hand transmitter Small S3
Sesam 800**

3-channel hand transmitter,
869.8 MHz

020439-31-3-32



**Hand transmitter Medium M6
Sesam 800**

6-channel hand transmitter,
869.8 MHz

020440-31-3-32



**Hand transmitter Large L15
Sesam 800**

15-channel hand transmitter,
869.8 MHz

020441-31-3-32



**Hand transmitter Large L99
Sesam 800**

99-channel hand transmitter,
869.8 MHz

020450-31-3-32



Sesam 800 wall receiver

230 V, BNC antenna included

020442-31-3-32




Sesam 800 wall receiver

24 V, BNC antenna included

020459-31-3-32

STANDARD


GENERAL



All-purpose torque arm

For fixing NovoShaft operators

150463-38-1-50



Extension chain NovoShaft

For version "Fast Chain" (1 m)

020271-31-3-32



4 m Shift cable extension

For version "Unlocking" / "Fast Chain", fixing material and grab handles included

020338-31-3-32



Chain conversation complete set 25.40

For ø 25.40 mm quill shaft

153319-01-1-50



Spiral cable system (0.6 / 3 m)

For NovoShaft, complete with connecting box

153236-02-1-50



Optical closing edge protection

For NovoShaft and GTA 803 S, transmitter and receiver, with connecting box and spiral cable

153232-01-1-50



Gear heating

For NovoShaft

020304-31-3-32



Feather key

For ø 25.4 mm quill shaft ⁽¹⁾,
6.35 x 6.35 x 130 solid shaft ⁽²⁾,
6.35 x 9.25 x 130 solid shaft ⁽³⁾

⁽¹⁾ 150463-39-1-50

⁽²⁾ 020344-31-3-32

⁽³⁾ 020296-31-3-32



Shaft adapter Hörmann

D40 / D25.4

020809-31-3-32



Main switch

For T 100, with cabling

150463-84-1-50



Key switch

For T 100, with cabling

153265-01-1-50



Control wire

For digital limit switch NovoShaft and GTA 4000, lengths: 3 - 25 m

153349-01-1-50

STANDARD


GENERAL



Savecoder

For electro-hydraulic hinged gate operators


020377-31-3-32



Housing for S 800 H

Laminated door carrying housing made of steel sheet with satined stainless steel cover

020370-31-3-32



Housing for S 800 H

Stainless steel

020371-31-3-32



Crown sleeve

For S 800 H

020384-31-3-32



Emergency release for S 800 H

For S 800 H, with crown sleeve

020395-31-3-32



Mounting kit for gatecoder

For underground hinged gate operators

020390-31-3-32



Hydraulic oil

1 litre

050441-31-3-32



Universal electric lock type SV

Prepared for profile half-cylinder

050509-31-3-32



Ground plate

For electric lock

050510-31-3-32



Electric lock type Mini

For narrow post installation, for profile half-cylinder

020242-31-3-32



Bolt lock

Electromechanic

147076-01-1-50




Hydraulic set

2 x 1500 mm tubes

050361-33-3-32


GENERAL



Base plate

For operators 746 and 844

020386-31-3-32




Profiles for NovoGate

C-profile ⁽¹⁾ for take in the end
profiles of the gate and end profile
(1 m) ⁽²⁾

⁽¹⁾ 152013-01-1-50

⁽²⁾ 152014-01-1-50




Toothed rack

Metal, 1 m

050469-31-3-32


SAFETY

SAFETY STRIPS



Safety strip system 1 - 35/50 - For sectional doors and roller shutters

Rubber profile: B 35 mm,
H 46.5 mm
Alu profile: B 35 mm,
H 18.0 mm
Total height: 64.5 mm



Safety strip STSU-1 (end strip) 8,2 kΩ

Connection cable 1 x 3 m

152100-01-1-50

Safety strip STSU-1 (end strip) 1,2 kΩ


For GTA 4000,
connection cable 1 x 3 m

152100-01-1-50

Safety strip STSU-2 (through strip)


Connection cable 2 x 3 m

152102-01-1-50



Safety strip system 2 - 35/70 - For sliding gates

Rubber profile: B 35 mm,
H 70.0 mm
Alu profile: B 35 mm,
H 18.0 mm
Total height: 88.0 mm



Safety strip STSU-1 (end strip) 8,2 kΩ

For NovoGate,
connection cable 1 x 3 m

152103-01-1-50

Safety strip STSU-1 (end strip) 1,2 kΩ

Connection cable 1 x 3 m

152104-01-1-50

Safety strip STSU-2 (through strip)

Connection cable 2 x 3 m

152105-01-1-50


ACCESSORIES FOR SAFETY STRIPS



Evaluation unit ESA 25-1

For safety contact strips with
8,2 kΩ, 1-channel AP-housing

050637-31-3-32



Inductive transmission system with evaluation unit

For safety strips with 8,2 kΩ

050916-31-3-32

TRAFFIC & WARNING LIGHTS

**Traffic light control A 800 III**

With 10 m connecting cable,
without radio receiver

150130-03-1-50

**Warning light LED**

Flashing or steady light adjustable,
with holder in green ⁽¹⁾, red ⁽²⁾ or
yellow ⁽³⁾, 24 V AC/DC or 230 V

⁽¹⁾ 148249-01-1-50

⁽²⁾ 148249-02-1-50

⁽³⁾ 148249-03-1-50

**Warning light LED red**

Flashing or steady light adjust-
able, 24 V AC/DC

148760-01-1-50

**Optical closing edge protection**

Transmitter, receiver, evaluation
electronics, socket and spiral
cable, 24 V

020014-31-3-32

LIGHT BARRIER

**Integrated light barrier LS 2-I**

2-wire, operating distance up to
8 m, for indoor use

148248-01-1-50

**Light barrier LS 2-A**

2-wire, operating distance 8 m,
for outdoor use

020303-31-3-32

**Light barrier LS 20-A**

4-wire, operating distance 20 m,
for outdoor use

020358-31-3-32

**Light barrier LS 5F**

Extra 625, operating distance 8 m

020412-31-3-32

**Light barrier FAAC XP 15B**

2-wire BUS system, operating
distance 15 m

020415-31-3-32

**Radio system light barrier
XP20WD**

2-wire BUS system, 24 V, IP 54, op-
erating distance 20 m, 24 V AC/DC,
optic rotatable, wireless: optionally

020457-31-3-32

**Reflection light barrier RLK**

Extra 628, operating distance 8 m

150463-54-1-50

**Wicket door contact**

Mechanical ⁽¹⁾, or magnetical ⁽²⁾,
with accessories

⁽¹⁾ 150450-01-1-50

⁽²⁾ 150450-04-1-50